


# A 151 - P 151

PLASMA RANGE



## TECHNICAL DATA

Voltage class	M
Standard length m	6
Air consumption	230 l/min
Air pressure	5 bar
Duty cycle 60%	150 A
Duty cycle 100%	120 A



**A 151** m

<b>FITTING</b>	<b>PA1552</b>	6
<b>1/4 G</b>	<b>PA1550</b>	6
<b>FITTING</b>	<b>PA1551</b>	12
<b>M14x7</b>	<b>PA1554</b>	6
	<b>PA1555</b>	12

Central adaptors



**P 151** m

<b>FITTING</b>	<b>PA0127</b>	6
	<b>PA0128</b>	12
<b>FITTING</b>	<b>PA0252</b>	6
<b>M14x7</b>	<b>PA0253</b>	12

Central adaptors

### DECLARATION OF CONFORMITY

The undersigned company Trafimet - Via del Lavoro, 8 - 36023 Castegnero (VI) - Italy - declares that the product identified and described on this page complies with standard EN 60974-7 in accordance with the requirements contemplated by directive EEC 73/23 low voltage.



EN 60974-7

*trafimet*<sup>®</sup>

*your welding partner*

**COMPLETE CABLE**

- PH0148 M14x1 6m
- PH0150 M14x1 12m
- PH0149 1/4 G 6m
- PH0151 1/4 G 12m

